

☛ Sprinklers

The table below will help you evaluate your water usage. The values listed below are for new heads that have not been damaged through long-term use by grit suspended in irrigation water. The table also presumes that the system employing the sprinklers is non-leaking. The gray cells show average user range.

	3/32"	1/8"	9/64"	5/32"	11/64"	3/16"	13/64"	7/32"
PSI	GPM	GPM	GPM	GPM	GPM	GPM	GPM	GPM
20	1.17	2.09	2.65	3.26	3.92	4.69	5.51	6.37
25	1.31	2.34	2.96	3.64	4.38	5.25	6.16	7.13
30	1.44	2.56	3.26	4.01	4.83	5.75	6.80	7.86
35	1.55	2.77	3.50	4.31	5.18	6.21	7.30	8.43
40	1.66	2.96	3.74	4.61	5.54	6.64	7.80	9.02
45	1.76	3.13	3.99	4.91	5.91	7.03	8.30	9.60
50	1.85	3.30	4.18	5.15	6.19	7.41	8.71	10.10
55	1.94	3.46	4.37	5.39	6.48	7.77	9.12	10.50
60	2.03	3.62	4.50	5.65	6.80	8.12	9.56	11.05
65	2.11	3.77	4.76	5.87	7.06	8.45	9.92	11.45
70	2.19	3.91	4.96	6.10	7.34	8.78	10.32	11.95
75	2.27	4.05	5.12	6.30	7.58	9.08	10.66	12.32
80	2.35	4.18	5.29	6.52	7.84	9.39	11.02	12.74
85	2.42	4.31	5.45	6.71	8.07	9.67	11.35	13.11
90	2.49	4.43	5.61	6.91	8.31	9.95	11.69	13.51
95	2.56	4.56	5.76	7.09	8.53	10.2	11.99	13.86
100	2.63	4.67	5.91	7.29	8.76	10.5	12.32	14.23